



**TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p.**  
**Technical and Test Institute for Construction Prague, SOE**

Akreditované zkušební laboratoře, Autorizovaná osoba, Notifikovaná osoba, Oznamovaný subjekt, Subjekt pro technické posuzování, Certifikační orgány, Inspekční orgán / Accredited Testing Laboratories, Authorized Body, Notified Body, Technical Assessment Body, Certification Bodies, Inspection Body • Prosecká 811/76a, Prosek, 190 00 Praha 9, Czech Republic

Notified Body 1020

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

No. 1020 – CPR – 090-039127

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

## ROAD RESTRAINT SYSTEM

Variant: Steel road safety barrier one-sided

**Passco L1 N2-B-W2 (ES 2.00) UK**

Level of restraint	<b>N2</b>
Impact intensity	<b>B</b>
Normalised working width	<b>W2</b>
Normalised vehicle intrusion	<b>NPD</b>
Snow removal	<b>NPD</b>

placed on the market under the name or trade mark of

**PASS+CO INTERNATIONAL GmbH**

Identification No.: DE811750759

Address: Dortmund Str. 8, 57234 Wilnsdorf/ Germany

and produced in the manufacturing plant

Code format PL1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 1317-5:2007+A2:2012/AC:2012**


under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

**constancy of performance of the construction product.**

This certificate was first issued on 21.07.2017 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The stamp of the Notified Body 1020  
Prague, 2<sup>nd</sup> September 2022



  
Martin Pešek  
Deputy Manager of the Notified Body

## Annex to certificate No. 1020 – CPR – 090-039127

## List of modification system

### Passco L1 N2-B-W2 (ES 2.00) UK

#### Modification 1: Equivalent usage of Profile A and Profile B

An equivalent usage of side beam "passco A-Profile material thickness 2,5 mm steel grade S355JR" and side beam "passco B-Profile material thickness 2,5 mm steel grade S355JR" is possible for the above-mentioned product.

#### Modification 2: Exchange of components

The geometrically equivalent side beams A/B Profiles (according to drawing RAL-RG 620 L1.1-101 and L1.1-102 respectively, dated 03/2010) are with the corresponding "passco A/B-Profiles" (according to drawing passco 2.1.4 and passco 2.1.1 respectively, dated 13.12.2011) interchangeable.

#### Modification 3: Equivalence of unalloyed structural steel S355JR and weather resistant structural steel COR-TEN B S355J2W/J0WP

The mechanical properties of the weather resistant structural steel hardly differ from similar unalloyed structural steels. Equivalent usage of unalloyed structural steel S355JR and weather resistant structural steel COR-TEN B S355J2W/J0WP is possible for the above-mentioned product.

#### Modification 4: Possible use of band galvanizing

The replacement of zinc coating applied on pieces through galvanizing according EN ISO 1461, with band galvanizing according to EN 10346 is possible for side beam A-Profile (RAL Part-No. 001.00) and B-Profile (RAL Part-No. 002.00) and for side beam "passco A-Profile" and "passco B-Profile" (material thickness 2.5 mm steel grade S355JR). This is valid to continuously hot-dip coated steel band corrosion protection systems with zinc (Z) (according to EN 10346-S250GD + 2600 NAC) and with zinc-aluminum (ZA) (according to EN 10346-S250GD and 24300 and 24600-NAC).

#### Modification 5: Exchange of fasteners

Based on the GD Tech report (PASS+CO/009) an equivalent usage of passco L1 post C100x60x25x5 from material S355 and bolt M10x45, 8.8 is possible for the above-mentioned product.

#### Modification 6: Exchange of AF beam


Based on the GD Tech report (PASS+CO/009) an equivalent usage of Beam switch from L1 A-profile to French A-profile is possible for the above-mentioned product.

#### Modification 7: Equivalent usage of 4 mm post

Based on the GD Tech report (PASSCO/2019/008 and PASSCO/2020/004) an equivalent usage of post with thickness 4mm is possible for the above-mentioned product.

The stamp of the Notified Body 1020  
Prague, 2<sup>nd</sup> September 2022



  
Martin Pešek  
Deputy Manager of the Notified Body